



SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID: DISPER-SUL 90% Pastille, 85% Pastille
Product Name: DISPER-SUL 90% Pastille, 85% Pastille
Revision Date: Mar 30, 2017 **Date Printed:** May 15, 2017
Version: 3.0 **Supersedes Date:** Jun 11, 2015
Manufacturer's Name: Martin Operating Partnership, L.P.
Address: P.O. Box 191, Kilgore, TX, US, 75663
Emergency Phone: CHEMTREC (800) 424-9300
Information Phone Number: 800-231-4595
Fax:
Product/Recommended Uses: Fertilizer

SECTION 2) HAZARDS IDENTIFICATION

Classification:

Skin Irritation - Category 2
Eye Irritation - Category 2A
Flammables solids - Category 2
Acute toxicity Inhalation - Category 4

Pictograms:



Signal Word:

Warning

Hazardous Statements - Physical:

Flammable solid

Hazardous Statements - Health:

Causes skin irritation
Causes serious eye irritation
Harmful if inhaled

Precautionary Statements - General:

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.

Precautionary Statements - Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
Wear protective gloves/protective clothing/eye protection/face protection.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof (electrical/ventilating/lighting) equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response:

IF ON SKIN: Wash with plenty of water.
Specific treatment (see First-aid measures on this label).
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing. And wash it before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use dry chemical, foam, carbon dioxide to extinguish.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.

Precautionary Statements - Storage:

No precautionary statement available.

Precautionary Statements - Disposal:

No precautionary statement available.

SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0007704-34-9	SULFUR	78% - 99%
0001302-78-9	BENTONITE	0.0% - 15%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell or are concerned. Eliminate all ignition sources if safe to do so.

Skin Contact:

Take off immediately contaminated clothing. Rinse skin with water/shower (and mild soap) for 15-20 minutes or until product is removed. Store contaminated clothing under water and wash before re-use, or discard.

Eye Contact:

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion:

Rinse mouth. If you feel unwell or if concerned: Get medical advice/attention. Do not induce vomiting without advice from poison control center.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use dry chemical, foam, carbon dioxide and Water (fog, fine spray pattern or steam) to extinguish fire

Unsuitable Extinguishing Media:

Use of water under high pressure streams must be avoided because risk of splattering or causing a steam explosion. Water fog, fine spray or steam can be used to reduce the material below its flash point, therefore extinguishing the fire.

Specific Hazards in Case of Fire:

Molten sulfur can release hydrogen sulfide, a highly toxic gas.
Fire may produce irritating and/or toxic gases.
Easily ignitable, combustible solid. Dust suspended in air ignites easily and can cause an explosion.
Hazardous in contact with oxidizing materials, forming explosive mixtures.
Sulfur burns with a pale blue flame that may be difficult to see in daylight.

Molten liquid can burn if heated to temperatures in excess of flash point.

Fire-fighting Procedures:

Clear fire area of all non-emergency personnel

Liquid sulfur in open containers may be extinguished with a fine spray of water.

Fires in storage tanks can be extinguished by shutting off vents to exclude air. Allow tank contents to cool to below 310°F before opening again.

Special Protective Actions:

Care should always be exercised in dust/mist areas.

Structural firefighters' protective clothing will only provide limited protection. Wear protective pressure self-contained breathing apparatus (SCBA).

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure:

Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material.

Stay upwind; keep out of low areas.

Flammable/combustible material.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Small/Large spill: With clean shovel place material into clean, dry container and cover loosely; move containers from spill area. If liquid spill, take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Prevent entry into waterways, sewers, basements or confined areas.

Collect product and contaminated soil and water.

Recommended equipment:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Personal Precautions:

Powders, dusts, shavings, borings, turnings or cuttings may explode or burn with explosive violence. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Use explosive proof equipment.

Avoid inhalation of dust and contact with skin and eyes.

Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

This product is a fertilizer, and if discarded to waterways, may promote algae growth/eutrophication.

SECTION 7) HANDLING AND STORAGE

General:

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Use explosion-proof ventilation equipment.

Storage Room Requirements:

Empty containers may contain residue; observe all warnings and precautions listed for the product.

Store in tightly closed containers in cool, dry, well-ventilated area away from heat, sources of ignition and incompatibilities.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection:

Dust-proof goggles or safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage.

Skin protection:

Avoid skin contact. Wear gloves impervious to conditions of use such as neoprene or nitrile gloves. Additional protection may be necessary to prevent skin contact including use of apron, face shield, boots or full body protection.

Respiratory protection:

If exposure limits are exceeded, NIOSH approved respiratory protection should be used. For higher concentrations, unknown concentrations, use a NIOSH approved air-supplied respirator.

Control Parameters / Exposure Limits:

Sulfur: OEL-RUSSIA: TWA 6mg/m3, JUN 2003

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
---------------	----------------	------------------	-----------------	-------------------	--------------------------	-----------------	-----------------------	-----------------	-------------------	------------------	--------------------	------------------

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
---------------	-----------------	-------------------	------------------	--------------------	------------------	-----------------	-----------------

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	15.61 lb/gal
% Solids By Weight	99.57%
Specific Gravity	1.87
<hr/>	
Appearance	Yellowish solid
Odor Threshold	N.A.
Odor Description	Odorless
pH	N.A.
Water Solubility	Insoluble
Flammability	Flash Point at or above 200 °F
Flash Point Symbol	N.A.
Flash Point	370 °F
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.
Freezing Point	N.A.
Melting Point	246 °F
Low Boiling Point	831 °F
High Boiling Point	N.A.
Auto Ignition Temp	491 °F
Decomposition Pt	N.A.
Evaporation Rate	Negligible
Partition Coefficient: n-Octanol/Water	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability:

Stable

Conditions to Avoid:

Avoid great heat, sparks, flame, build up of static electricity, contact with incompatible materials.

Hazardous Polymerization:

Will not occur.

Incompatible Materials:

Material may be corrosive to ferrous and mild steel materials. All handling and storage equipment should be constructed of stainless steel, aluminum, or poly-type materials. Powdered sulfur is subject to dust cloud explosions.

Incompatible with acids, alkalis, halogens, oxygen and strong oxidizing agents.

Forms explosive mixtures with oxidizing agents, ammonia, ammonium nitrate, chlorine dioxide, all inorganic perchlorates, sodium nitrate, and zinc.

Hazardous Decomposition Products:

Sulfur oxides, hydrogen sulfide.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation:

Causes skin irritation

Serious Eye Damage/Irritation:

Causes serious eye irritation

Respiratory/Skin Sensitization:

No Data Available

Germ Cell Mutagenicity:

No Data Available

Carcinogenicity:

No Data Available

Reproductive Toxicity:

No Data Available

Specific Target Organ Toxicity - Single Exposure:

No Data Available

Specific Target Organ Toxicity - Repeated Exposure:

No Data Available

Aspiration Hazard:

No Data Available

Acute Toxicity:

Harmful if inhaled

0007704-34-9 SULFUR

LC50 (Mammal - species unspecified, Inhalation) : 1660 mg/m3, Toxic effects : Details of toxic effects not reported other than lethal dose value.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity:

No Data Available

Persistence and Degradability:

No Data Available.

Bioaccumulative Potential:

No Data Available.

Mobility in Soil:

No Data Available.

Other Adverse Effects:

No Data Available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information:

Packaging references: Exempt from requirements (49CFR172.102, Special Provision 30)

Commodity Name: Solid sulfur product

Shipping Description: Solid sulfur product

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0007704-34-9	SULFUR	78% - 99%	SARA312,TSCA,TX_ESL,TX_TCEQ
0001302-78-9	BENTONITE	0.0% - 15%	SARA312,TSCA,TX_ESL,TX_TCEQ

SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

Glossary:

ACGIH: American Conference of governmental Industrial Hygienists; ANSI: American National Standards Institute; Canadian TDG: Canadian Transportation of Dangerous Goods; CAS: Chemical Abstract Service; Chemtrec: Chemical Transportation Emergency Center (US); CHIP: Chemical Hazard Information and Packaging; DSL: Domestic Substances List; EC: Equivalent Concentration; EH40 (UK): HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA: Emergency Planning and Community Right-To-Know Act; HMIS: Hazardous Material Information Service; LC: Lethal Concentration; LD: Lethal Dose; NFPA: National Fire Protection Association; OEL: Occupational Exposure Limits; OSHA: Occupational Safety and Health Administration, US Department of Labor; PEL: Permissible Exposure Limit; SARA (Title III): Superfund Amendments and Reauthorization Act; SARA 313: Superfund Amendments and Reauthorization Act, Section 313; SCBA: Self-Contained Breathing Apparatus; STEL: Short Term Exposure Limit; TLV: Threshold Limit Value; TSCA: Toxic Substances Control Act Public Law 94-469; TWA: Time Weighted Value; US DOT: US Department of Transportation; WHMIS: Workplace Hazardous Materials Information System


Version 2.0:

Changes made on: Section 2, Section 5, Section 7, Section 9 and Section 11

Revision Date: Jul 14, 2015

Please contact the supplier for further information on the version history

HMIS	
Health	/ 1
FLAMMABILITY	1
Physical Hazard	1
Personal Protection	



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 3.0:

Revision Date: Mar 30, 2017

DISCLAIMER

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Martin Operating Partnership L.P.'s knowledge; however, Martin Operating Partnership L.P. makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Martin Operating Partnership L.P. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Martin Lubricants, a division of Martin Operating Partnership L.P., must rely upon information provided by the material manufacturers or distributors.